

BARRIER GATE SYSTEM · MAGNETIC PARKING PRO

PARKING LOT LANE



SPECIFICATIONS

Model	Magnetic Parking Pro
Max lane width (model)	11.5 ft
Opening time	1.3 s
Design life	10 million
Controller	MGC Pro
UL 325	Certified to UL 325
Duty cycle	100%
Drive	MHTM™ direct drive — maintenance-free, quiet
Enclosure	IP54
Operating temperature	-22 to 131 °F
Vehicle detection	Built-in 2-channel loop detector
Safety input	Photo eye / safety scanner
Model options	Folding arm available (see Parking Garage Lane) · Breakaway flange — optional accessory · Tailgate detection — standard
Power input	85–264 VAC, 50/60 Hz (runs on a standard 120 V circuit)
Max power	95 W
Rated current	1.5 A · 120 V, 60 Hz
I/O	8 in · 6 relay + 4 digital out
Loop detector	Built-in 2-channel
Lane widths offered	8 ft · 10 ft · 11.5 ft
Arm styles	Straight / Folding

Questions? 855-526-9683 · Sales@CoyoteTraffic.com · www.CoyoteTraffic.com

Magnetic barrier gates are designed and built in Germany by Magnetic Autocontrol, a FAAC Group company.



WHAT'S IN THE BOX — COMPLETE LANE

- Magnetic Parking Pro operator
- Straight striped boom
- 2 vehicle loops
- Photo eye

OPERATOR + ARM ONLY

- Magnetic Parking Pro operator
- Straight striped boom

ENTRAPMENT PROTECTION (UL 325) · CLASS II

Class II: public and HOA sites, five or more units

Certified to UL 325

Two independent entrapment devices required: vehicle loops plus photo eye — both included with the complete lane.

PRICING

Complete lane \$6,320

Operator + arm only \$4,279

+ \$295 LTL freight per order · residential liftgate one-time \$95 · USD, tax not included · prices as of October 28, 2026